
Product Information Sheet Z341 Manual Food Can Coating Analyser





ELECTRICITY 100-240 Volts / 50-60 Hz



COMPRESSED AIR N/A



Estimated 25kg

(W) 630.5mm x (H) 252mm (D) 300mm

Torus Measurement Systems Ltd | Nedge Hill Science Park, Telford, TF3 3AJ, UK | Tel: +44 (0) 1952 210 020 | sales@torus-group.com Torus Americas, Inc | 150 Capital Drive, Suite 340-350, Golden, Colorado, 80401, USA | Tel: +1-303-384-0279 | tai.sales@torus-group.com | www.torus-group.com

The Torus Measurement Systems Manual Coating Analyser has been developed to give fast and accurate measurement of the internal lacquer, sprayed during today's 2 and 3 piece can manufacturing process.

By cutting the can to give suitable access, the dome area of the can is able to be checked by the system.

No "lacquer panels" are required for calibration and measurement data can be exported via on board USB or LAN ports to your factory data acquisition systems where required.

Gauge Features:

Dual system equipped with two spectrometers -

> Visible light and Near Infrared (NIR) light, enables the OV/over ink inspection

Measurement Features:		
Feature	Accuracy	Capability
Internal Lacquer	+\- 0.2 μ m	0.4 µm
Over Varnish	+\- 0.2 μ m	0.4 µm

Technical Specification:		
Capabilities	Typical Range	
Body Diameter	Ø < 35 mm	



remen

Benefits to your business

- Simple, manual positioning by the operator ensures side wall measurements are immediately displayed on the embedded mini touch screen PC
- Cans from (202) (307) body diameter can be accomodated by the systems "scissor" action location fingers, operated at the push of a button
- "Non-contact" means no wear parts, and the use of a non-contact "white light spectroscopy" technique guarantees unprecedented performance

